






V9944

(*)				
T	°C	-50 +280 (1)		
p	bar	60	40	20
V	m/s	1.5	2	15
pH		2 + 12		



(*) Do not use the product to the maximum temperature and pressure associated without consult the manufacturer

Average Composition

- E glass fiber
- PTFE impregnation
- Lubricant silicon free

Features

Made from 6-micron E glass fibers, increased to 9 micron through a special process and lightly twisted. This packing is impregnated with a particular compound based on concentrated PTFE together with inert, silicon free lubricant.

Applications

Suitable with water, steam, oils, solvents and almost all abrasive and crystallizing chemical products.

size mm	size inch	kg/box	lbs/box	mt/box	ft/box	mt/kg	ft/lbs
3,0	1/8	1,0	2,2	61,7	203	61,7	91,9
4,0	-	1,0	2,2	34,7	114	34,7	51,7
5,0	3/16	1,0	2,2	22,2	73	22,2	33,1
6,0	-	2,5	5,5	38,6	127	15,4	23,0
6,5	1/4	2,5	5,5	32,9	108	13,1	19,6
8,0	5/16	2,5	5,5	21,7	71	8,7	12,9
9,5	3/8	2,5	5,5	15,4	50	6,2	9,2
10,0	-	2,5	5,5	13,9	46	5,6	8,3
11,0	7/16	2,5	5,5	11,5	38	4,6	6,8
12,0	-	2,5	5,5	9,6	32	3,9	5,7
12,7	1/2	2,5	5,5	8,6	28	3,4	5,1
14,0	9/16	5,0	11,0	14,2	46	2,8	4,2
16,0	5/8	5,0	11,0	10,9	36	2,2	3,2
17,5	11/16	5,0	11,0	9,1	30	1,8	2,7
18,0	-	5,0	11,0	8,6	28	1,7	2,6
19,0	3/4	5,0	11,0	7,7	25	1,5	2,3
22,0	7/8	5,0	11,0	5,7	19	1,1	1,7
25,5	1	5,0	11,0	4,3	14	0,9	1,3

packaged +/- 10 % in weight