

Camlock kobling type A

Camlock kobling type A, HAN med indvendigt rørgvind.

Varianter

Produkt nr.	Materiale	Gevind dimensioner "
SNAP0302	Polypropylen	½
SNAP0304	Polypropylen	¾
SNAP0306	Polypropylen	1
SNAP0308	Polypropylen	1 ¼
SNAP0310	Polypropylen	1 ½
SNAP0315	Polypropylen	2
SNAP0320	Polypropylen	3
SNAP1305	Aluminium	½
SNAP1315	Aluminium	¾
SNAP1320	Aluminium	1
SNAP1325	Aluminium	1 ¼
SNAP1330	Aluminium	1 ½
SNAP1335	Aluminium	2
SNAP1340	Aluminium	2 ½
SNAP1345	Aluminium	3
SNAP1350	Aluminium	4
SNAP1355	Aluminium	5
SNAP1360	Aluminium	6
SNAP2305	Rustfrit/syrefast stål	½
SNAP2315	Rustfrit/syrefast stål	¾
SNAP2320	Rustfrit/syrefast stål	1
SNAP2325	Rustfrit/syrefast stål	1 ¼
SNAP2330	Rustfrit/syrefast stål	1 ½
SNAP2335	Rustfrit/syrefast stål	2
SNAP2340	Rustfrit/syrefast stål	2 ½
SNAP2345	Rustfrit/syrefast stål	3
SNAP2350	Rustfrit/syrefast stål	4
SNAP2355	Rustfrit/syrefast stål	5
SNAP2360	Rustfrit/syrefast stål	6
SNAP3305	Messing	½
SNAP3315	Messing	¾
SNAP3320	Messing	1
SNAP3325	Messing	1 ¼
SNAP3330	Messing	1 ½
SNAP3335	Messing	2
SNAP3340	Messing	2 ½
SNAP3345	Messing	3
SNAP3350	Messing	4
SNAP3355	Messing	5
SNAP3360	Messing	6

