

Klokobling - luft

- Klokobling til luft
- Kloafstand: 42 mm
- Temperatur: - 40 til 95°C
- Maks. arbejdsstryk: 10 bar
- Materiale: gulchromatiseret støbejern
- Pakning: NBR (varenr. KLOKGOER)

Varianter



Produkt nr.	Beskrivelse	Studs mm
KLOSKG06	Klokobling m. slangestuds	¼"
KLOSKG08	Klokobling m. slangestuds	5/16"
KLOSKG10	Klokobling m. slangestuds	3/8"
KLOSKG13	Klokobling m. slangestuds	½"
KLOSKG19	Klokobling m. slangestuds	¾"
KLOSKG25	Klokobling m. slangestuds	1"
KLOSKG32	Klokobling m. slangestuds	1 ¼"



KLOKIG14	Klokobling m. IRG	¼"
KLOKIG38	Klokobling m. IRG	3/8"
KLOKIG12	Klokobling m. IRG	½"
KLOKIG34	Klokobling m. IRG	¾"
KLOKIG10	Klokobling m. IRG	1"
KLOKIG54	Klokobling m. IRG	1 ¼"



KLOKAG14	Klokobling m. URG	¼"
KLOKAG38	Klokobling m. URG	3/8"
KLOKAG12	Klokobling m. URG	½"
KLOKAG34	Klokobling m. URG	¾"
KLOKAG10	Klokobling m. URG	1"
KLOKAG54	Klokobling m. URG	1 ¼"



KLOKOVK0 Blindkobling uden kæde

Produkt nr.	Materiale	Anvendelse	Farve	Temp.	Sh.A
KLOKGOER	NBR	Luft	Sort	-40 - +95 °C	65°
KLOKGDOR	TFEP	Damp	Rød	-15 - +200 °C	65°
KLOKGVOR	FKM/Viton	Kemi	Grøn	-40 - +200 °C	50°

