

Camlock kobling type F

Camlock kobling type F, HAN med udvendigt rørgvind.

Varianter

Produkt nr.	Materiale	Gevind dim. "
SNAP0402	Polypropylen	½
SNAP0404	Polypropylen	¾
SNAP0406	Polypropylen	1
SNAP0407	Polypropylen	1 ¼
SNAP0410	Polypropylen	1 ½
SNAP0415	Polypropylen	2
SNAP0420	Polypropylen	3
SNAP1405	Aluminium	½
SNAP1415	Aluminium	¾
SNAP1420	Aluminium	1
SNAP1425	Aluminium	1 ¼
SNAP1430	Aluminium	1 ½
SNAP1435	Aluminium	2
SNAP1440	Aluminium	2 ½
SNAP1445	Aluminium	3
SNAP1450	Aluminium	4
SNAP1455	Aluminium	5
SNAP1460	Aluminium	6
SNAP2405	Rustfrit/syrefast stål	½
SNAP2415	Rustfrit/syrefast stål	¾
SNAP2420	Rustfrit/syrefast stål	1
SNAP2425	Rustfrit/syrefast stål	1 ¼
SNAP2430	Rustfrit/syrefast stål	1 ½
SNAP2435	Rustfrit/syrefast stål	2
SNAP2440	Rustfrit/syrefast stål	2 ½
SNAP2445	Rustfrit/syrefast stål	3
SNAP2450	Rustfrit/syrefast stål	4
SNAP2455	Rustfrit/syrefast stål	5
SNAP2460	Rustfrit/syrefast stål	6
SNAP3405	Messing	½
SNAP3415	Messing	¾
SNAP3420	Messing	1
SNAP3425	Messing	1 ¼
SNAP3430	Messing	1 ½
SNAP3435	Messing	2
SNAP3440	Messing	2 ½
SNAP3445	Messing	3
SNAP3450	Messing	4
SNAP3455	Messing	5
SNAP3460	Messing	6

