

VLU-300

Geotextile for protect and water retain functions

#320416



Technical Data Sheet

■ Green up the roof!

	Rot-proof mechanical protection layer thermally treated on both sides made of 100 % synthetic fibres. Water permeability: 90 mm/s; Surface weight: 300 g/m ² ; tensile strength weft: 2,2 KN/m; tensile strength warp: 3,2 KN/m; robustness class: GRK 2; colour: Multicolour; packaging: 100 m ² /roll; packaging weight: 30 kg/roll. Tested in accordance with: FLL guidelines 5.3/2002; 8.2/2002 Protection and filter fleece; MSZ 93-9:1985 Water retention capacity; EN ISO 12956 Opening width; EN 918 CBR; EN ISO 12236 Elasticity; EN ISO 10319 Tensile strength; EN ISO 11058 Water permeability.	
	Dim.	VLU-300
Width	m	2,0 (roll width)
Lenght	m	50 (roll lenght)
Thickness	mm	1,8
Diameter	cm	~37 (roll diameter)
Weight	kg	30 (roll weight)
Surface weight	g/m ²	300
Density	g/cm ³	0,9-1,38
Melting point	°C	110-260
Tensile strenght weft	KN/m	2,7
Tensile strenght warp	KN/m	3,7
CBR-test, strenght	N	1000

Reviewed: 2011-07-01 09:28:16

Specifications are subject to change without notice.

APP Kft.

H-9028 Győr, Fehérvári út 75.

Email: info@diademroof.com; Web: www.diademroof.com